

## § 109.435

(g) The date of each inspection of each accommodation space.

(h) The date of each inspection required in §109.573 if performed by the master or person in charge.

[CGD 73-251, 43 FR 56828, Dec. 4, 1978, as amended by CGD 83-067, 49 FR 39162, Oct. 4, 1984; CGD 89-037, 57 FR 41824, Sept. 11, 1992; CGD 84-069, 61 FR 25303, May 20, 1996]

### § 109.435 Record of fire fighting equipment inspection.

(a) The master or person in charge shall ensure that a record of each test and inspection required in §109.223 is maintained on board, until the unit is reinspected or inspected for certification.

(b) The record required in paragraph (a) of this section must show—

(1) The date of each test and inspection;

(2) The number or other identification of each item of equipment tested or inspected; and

(3) The name of the person, and the company he represents if any, who conducts the test or inspection.

### § 109.437 Crane record book.

The master or person in charge shall ensure that the following are maintained in a crane record book:

(a) Descriptive information which will identify each crane including—

(1) The API name plate data required by Section 11 of API Spec. 2C, Second Edition, February 1972; and

(2) The rated load chart for each line reeving and boom length which may be utilized.

(b) Information required by Section 3 of the American Petroleum Institute *Recommended Practice for Operation and Maintenance of Offshore Cranes*, API RP 2D, First Edition (October 1972) with supplement 1.

(c) Dates and results of frequent inspections and tests required in paragraph (b) of this section.

(d) Dates and results of periodic inspections and tests required in paragraph (b) of this section.

(e) Date and result of each rated load test.

(f) Date and description of each replacement or renewal of wire rope, hooks, and other load components.

## 46 CFR Ch. I (10-1-03 Edition)

(g) Date and description of each failure of the crane, or any component or safety feature.

(h) Date and description of each repair to the crane structure, boom, or equipment.

### § 109.439 Crane certificates.

The master or person in charge shall insure that the following certificates and records for each crane are maintained on the unit:

(a) Each certificate issued by a crane certifying authority.

(b) Each record and original certificate, or certified copy of a certificate, or manufacturers or testing laboratories, companies or organizations for—

(1) Loose gear;

(2) Wire rope; and

(3) The annealing of wrought iron gear.

## Subpart E—Emergency Signals

### § 109.503 Emergency signals.

(a) Emergency stations signals are established as follows:

(1) The signal to man emergency stations is a rapid succession of short soundings of both the general alarm bell and the whistle, if a whistle is installed, for a period of not less than 10 seconds.

(2) The signal to secure from emergency stations is the sounding of both the general alarm bell and the whistle, if a whistle is installed, three times.

(b) The abandon unit stations signals are established as follows:

(1) The signal to man abandon unit stations is a continuous sounding of both the general alarm and the whistle, if a whistle is installed.

(2) If whistle signals are used to direct the handling of lifeboats and davit-launched liferafts, they must be—

(i) One short blast to lower the lifeboats and davit-launched liferafts; and

(ii) Two short blasts to stop lowering the lifeboats and davit-launched liferafts.

(3) The signal to secure from abandon unit stations is the sounding of both

## Coast Guard, DHS

## § 109.563

the general alarm bell and the whistle, if a whistle is installed, three times.

[CGD 73-251, 43 FR 56828, Dec. 4, 1978, as amended by CGD 84-069, 61 FR 25303, May 20, 1996]

### Subpart F—Cranes

#### § 109.521 Cranes: General.

The master or person in charge shall ensure that each crane is operated and maintained in accordance with the API *Recommended Practice for Operation and Maintenance of Offshore Cranes*, API RP 2D, First Edition (Oct. 1972) with supplement 1.

#### § 109.525 Cranes: Working loads.

The master or person in charge shall ensure that tables indicating the maximum safe working loads for the various working angles of the boom, where the boom is rated at varying capacities depending on the radius, and the maximum and minimum radius at which the boom may be safely used, are conspicuously posted near the controls and are visible to the operator when working the crane.

#### § 109.527 Cranes: Operator designation.

(a) The master or person in charge shall designate, in writing, each crane operator.

(b) The master or person in charge shall ensure that only designated operators operate cranes.

(c) The master or person in charge shall ensure that each designated operator is familiar with the provisions of the API *Recommended Practice for Operation and Maintenance of Offshore Cranes*, API RP 2D, First Edition (Oct. 1972) with supplement 1.

### Subpart G—Miscellaneous

#### § 109.555 Propulsion boilers.

The master or person in charge and the engineer in charge shall ensure that—

(a) Steam pressure does not exceed that allowed by the certificate of inspection; and

(b) The safety valves, once set, are not tampered with or made inoperative.

[CGD 73-251, 43 FR 56828, Dec. 4, 1978, as amended by CGD 95-028, 62 FR 51208, Sept. 30, 1997]

#### § 109.557 Flammable and combustible liquids: Carriage.

The master or person in charge shall ensure that—

(a) Flammable and combustible liquids in bulk are not carried, except as allowed by endorsement to the Certificate of Inspection;

(b) Portable tanks are handled and stowed in accordance with subparts 98.30 and 98.33 of this chapter and the provisions of 49 CFR parts 171 through 179 that apply to portable tanks; and

(c) Grades B and lower liquids are—

(1) Authorized, by the Commandant, to be carried; and

(2) Carried only in fixed independent or integral tanks.

[CGD 73-251, 43 FR 56828, Dec. 4, 1978, as amended by CGD 84-043, 55 FR 37413, Sept. 11, 1990]

#### § 109.559 Explosives and radioactive materials.

Except as authorized by the master or person in charge, no person may use explosives or radioactive materials and equipment on a unit.

#### § 109.563 Posting of documents.

The master or person in charge shall ensure that the following are posted under glass in the pilot house or control center:

(a) General arrangement plans for each deck showing—

(1) Each fire retardant bulkhead;

(2) Each fire detecting, manual alarm, and fire extinguishing system;

(3) Each fire door;

(4) Each means of ingress to compartments; and

(5) Each ventilating system, including the location of each damper, fan, and remote means of stopping the fans.

(6) For units constructed on or after September 30, 1997, and for existing units which have their plans redrawn, the symbols used to identify the aforementioned details shall be in accordance with IMO Assembly resolution A.654(16). The identical symbols can be